

Idemitsu Multi-Vehicle ATF PLUS

Description

Idemitsu Multi-Vehicle ATF PLUS is the latest advanced automatic transmission fluid suitable for use in all modern AT units. This special formulation enhances smooth & positive shifting under severe working conditions.

Application

Recommended for all modern AT transmission gearbox from Asian auto makers (Especially Japanese cars) to American, Continental and South Korean cars.

Characteristics

- Super long-life automatic transmission fluid.
- Superior protection against premature wear & tear of moving parts.
- Excellent protection and performance at high temperatures and high loads.

Compatible with:

•JASO 1A-LV (13), •AW-2, JWS3309, JWS3324 •D3-SP, •Type 3.0 & 3.1, DW-1, Z1 •ATF II, ATF III, ATF WSI •FZ, A7, M-V, M-III •DiaQueen AW, J2, J3, SP-II, SP-III, SP-IV, MA-1, PA •Matic-D, Matic-J, Matic-K, Matic-S, Matic-P, Matic-W, N402 •ATF-HP, ATF-WS •ATF2326, 2384K, 3314, 3317, 5D06 •ATF-FZ, T-III, T-IV, WS, D2 •C4, •3+, 4, 6, 7, ETL-7045E, -8072B, LA2634, LT71141, ML12108 •+3, +4, 8&9 speed ATF, AW-1, D-VI, SP-III, SP-4, MB236.10/12, Type 9602 •Merc, Merc LV, Merc SP, Merc ULV, Merc V • D-VI, D-IIIH, D HP, D ULV, AW-1 •SP-II, SP-III, SP-IV, SP-IVM •JLM20238, 20292, 21044, AW-1, LT71141, N402, •339A, 339D, 339F •Sheet 236.1, 236.10, 236.11, 236.12, 236.14, 236.15, 236.16, 236.17, 236.2, 236.41, 236.5, 236.82, ATF 3403-M115 •AL4, B71, Z •DP-0, Matic D2, SATF-D •1161521, 1161621, 1161640 •G052 162, G052 533, G052 990, G053 001, G055 005, G055 025, G055 162, G055 540, G060 162, G060 540, LT71141 •Lifeguard 5, 6, 8, 9, TE-ML11A/11B

Packing

24 x 1 Litre Carton, 200 Litres Drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Product Data Sheet

Typical Specifications

Idemitsu Multi-Vehicle ATF PLUS

ASTM METHOD

Color (Appearance)		Red
Density 15 °C g/cm ³	D-4052	0.8536
Flash Point (COC) °C	D-92	196
Viscosity, cSt @ 100 °C	D-445	6.1
BF Viscosity mPa-s @ -40 °C	D-2983	9,790
Pour Point °C	D-97	-55
TBN,HCl (mgKOH/g)	D-4739	1.90
Foaming @ 93.5°C (ml)	D-892	10-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.